

SAFETY DATA SHEET Issue: 1

According to Regulation (EU) No. 2015/830 From: 12.02.2020

1. Identification of the Mixture and of the Company/Undertaking

Product identity:

Polyramid BRV 30 BK10

Intended Use:

Pelletised polymer compound for manufacture of plastic articles

by injection moulding & extrusion processes.

Company:

Polyram UK Limited

Ward Industrial Estate

Church Road Lydney

Gloucestershire GL15 5EL

U.K.

Telephone:

[+44] (0) 1594 842406

Email:

enquiries@polyram-group.com

Emergency Telephone:

[+44] (0) 1594 842406

2. Hazards Identification

Classification of the substance or mixture

According to Regulation (EC) No. 1272/2008 as amended:

This product is not classified as a hazardous substance or mixture.

Label Elements:

No Special labelling is applicable.

Other Hazards:

Spilled pellets present a slip hazard. Clean up spills immediately.

3. Composition/Information on Ingredients

Chemical Description:

Polymer - Compounded mixture

Mixture components:

Polyamide 6, glass fibre reinforced + minor additives (Lubricant,

stabiliser, pigment)

Hazardous Components:

None classified according to CLP Regulation (EC) No. 1272/2008

4. First Aid Measures

Burns: Treat contact burns immediately by immersing or drenching the

affected area with cold water. Solid material remaining on the skin should not be pulled off but should be treated by qualified medical

staff.

Eye Contact: Irrigate copiously with water for at least ten minutes; obtain medical

advice immediately if irritation persists or there is any tissue

damage.

In the event of excessive inhalation of fumes remove the individual

to fresh air and keep at rest; obtain medical advice immediately.

In the event of accidental ingestion, rinse mouth with water; give up

to 1 tumbler (250 ml) of milk or water to drink; obtain medical advice

immediately.

5. Fire Fighting Measures

Extinguishing Media: Dry powder, foam or water spray.

Unsuitable Media: High pressure concentrated water jet may disperse flaming

particles.

Exposure Hazards: Toxic fumes will be evolved in a fire. Burning will be accompanied by

the release of flaming droplets of molten polymer. For

decomposition products see Section 10.

Protective Equipment: Fire fighters and others exposed, wear self-contained breathing

apparatus.

6. Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions:

Do not allow to enter drains and water courses.

Methods for Cleaning Up: Vacuum or sweep up. For disposal see Section 13.

7. Handling and Storage

Handling: The material, normally supplied as dust-free granules, should be

handled by procedures which do not lead to the generation of dust. Contains glass fibers. Avoid skin contact. Take precautionary measures against static discharges. Spilt materials should be cleaned

up immediately to avoid slipping and fall risks.

Storage: Material should be stored under dry, cool conditions in the original

sealed packaging until required for use.

On exposure to the atmosphere the material will absorb moisture possibly leading to foaming and spitting during processing unless suitably re-dried.

8. Exposure Controls/Personal Protection

Engineering Measures: Use Local Exhaust Ventilation to remove gases and vapours released

during drying, purging and moulding operations. Use Local Extraction to remove possible dust during finishing operations such as grinding

or machining.

Occupational Exposure

Limits (EH40): Total Inhalable Dust

Respirable Dust

10 mg/m³ - 8-hour TWA

4 mg/m³ - 8-hour TWA

Caprolactam (1,6-Hexanolactam)

Dust & Vapour

1 mg/m³ - 8-hour TWA

3 mg/m³ - 15-min. ref. period

Eyes:

Safety spectacles or goggles when machining mouldings.

Respiratory Protection:

Use suitable respiratory protection according to Regulation (EU) 2016/425 if operations create dust (DIN EN 143 particulate filter

P1).

Hand Protection:

Molten polymer derived from melt processing can adhere to the skin causing severe contact burns. Irritant fumes may be emitted during melt processing particularly if overheated - see Section 10.

Use heat resistant gloves (EN407) during melt processing and

moulding.

9. Physical and Chemical Properties

Appearance:

Black granules.

Odour:

None.

Specific Gravity:

Approx. 1.4 g/cm³

Soluble in:

Partially soluble in formic acid, sulphuric acid.

Insoluble in:

Water.

Melting Range:

215 - 225 °C.

Thermal Decomposition:

> 310 °C when typical good processing practices are followed. See

Section 10 - 'Conditions to avoid'.

10. Stability and Reactivity

Conditions to Avoid:

Storage at elevated temperatures and conditions of high humidity.

Use of excessive temperatures and / or prolonged delay exposures at normal processing temperatures may cause decomposition.

Hazardous Decomposition Products:

Thermal decomposition products may include ammonia, hydrogen cyanide, aldehydes and oxides of carbon and nitrogen.

11. Toxicological Information

Acute toxicity:

Not classified (No data available for this product).

Skin corrosion/irritation:

Not classified (No data available for this product).

Prolonged unprotected contact with dust or pellets may cause

localised irritation.

Serious eye damage:

/irritation

Not classified (No data available for this product).

Respiratory or skin:

sensitisation

Not classified (No data available for this product).

Germ cell mutagenicity:

Not classified (No data available for this product).

Carcinogenicity:

Not classified (No data available for this product).

Reproductive toxicity:

Not classified (No data available for this product).

STOT-single exposure:

Not classified (No data available for this product).

STOT-repeated exposure:

Not classified (No data available for this product).

Aspiration hazard:

Not classified (No data available for this product).

12. Ecological Information

Environmental Effects:

On the basis of available information, this product is not expected to produce significant adverse environmental effects if recommended

use instructions are followed.

The product is not considered to be biodegrabable.

Specific ecological data is not available for the product

13. Disposal Considerations

This product should preferably be recycled using typical thermoplastics regranulation & subsequent melt processing techniques whenever possible. When recycling is not a viable option, energy recovery via incineration or disposal to landfill may be considered. Local guidance and regulations must be followed.

_				
Recy	ICI	ing	COL	do.
1166		III IS	CU	JC.

>PA6-GF30<

(ISO

11469:2016))

14. Transport Information

The product is not classified by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID) and does not require special transport provisions.

15. Regulatory Information

EU Regulation (EC) No. 1907/2006 REACH:

The material contains no component substances currently restricted, subject to authorisation or candidate listed as SVHC (Substances of Very High Concern).

16. Other Information

Use:

This material is formulated for use as an injection moulding material and the advice contained in this datasheet is based on this processing method. If any other use is intended, advice should be sought from Polyram UK Limited.

Hazard phrases if full:

Not classified according to current EU regulations.

Risk Phrases in full:

Not classified according to current EU regulations.

SDS Revision No:

1

Issue Date:

12.02.2020

Superseded version:

New

Disclaimer

To the best of our knowledge, the information contained herein is correct and accurate but does not purport to be all inclusive and shall be used only as a guide. The information relates only to the specific material designated, Polyram UK Ltd, assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Polyram UK Ltd warrants only that the goods sold shall conform to Polyram UK Ltd standard specifications or such other mutually agreed-to and documented specification. This express warranty is in lieu of and excludes all other express warranties and is extended only to Buyer. Polyram UK Ltd EXPRESISY DISCLAIMS ALL OTHER WARRANTIES INCLUDING THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND MAKES NO WARRANTY AS TO THE RESULTS BUYER CAN EXPECT FROM BUYER'S USE OF THE GOODS. No employee or agent of Polyram UK Ltd is authorized to make warranties about goods sold by Polyram UK Ltd, and Buyer should not rely on any oral or written communications from employees or agents of Polyram UK Ltd that purport to constitute a warranty. Any assistance furnished by Polyram UK Ltd in the selection of goods or suggestions as to their processing or use are accepted by Buyer at Buyer's own risk, and Polyram UK Ltd shall not be liable to Buyer for results obtained by Buyer from such assistance or suggestions. In no event and under no circumstances will Polyram UK Ltd be liable for consequential damages of any kind.

-End of SDS-